

ORIENT BLACK[®] N330T

FURNACE BLACK

PRODUCT DESCRIPTION

Orient Black N330T is a Furnace Black grade featuring medium structure and medium surface area, offering high resilience, easy processing and moderate tensile strength properties.

APPLICATION

Orient Black N330T can be used in hoses and hose covers, tyre casings, solid tyres, conveyor belts, rollers and molded rubber goods, which require optimum balance of crack propagation, hysteresis, flexibility and viscosity properties.



RECOMMENDED APPLICATION

 Highly recommended  Recommended under advice  Not recommended



QUALITY PARAMETERS

Property	Unit	Typical value	Test method
STSA	m ² /g	71	ASTM D6556
Iodine Adsorption No.	g/kg	70	ASTM D1510
OAN	cm ³ /100g	103	ASTM D2414
COAN	cm ³ /100g	88	ASTM D3493
Tint Strength	Tint Unit	102	ASTM D3265
Ash Content	%	≤0.75	ASTM D1506
Heating Loss	%	≤1.5	ASTM D1509

PACKAGING

Packaging mode	Per unit qty. (kg)	No. of bags/40 ft. container
Paper Bag	25	960
Big Bag (FIBC)	1000	22

PRODUCT SAFETY

- Refer to SDS for handling purpose

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India

Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India

P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcbltd.com

E: pcbl.mktg-international@rpsg.in | pcbl.mktg-national@rpsg.in | pcbl.rubbertech@rpsg.in

